Hewlett Packard HPE Support Center Enterprise

HP StorageWorks NAS 1200s - Specifications

System and component specifications
Physical specifications
Electrical specifications

Environmental specifications

System and component specifications

Available models	320 GB, 640 GB and 1 TB (raw capacity)
CPU	Intel Pentium 4 2.4 GHz
Memory	512-MB 200 MHz PC2100 DDR SDRAM
PCI-X and PCI slots	64-bit
Hot pluggable hard drives	Four 80 GB, 160 GB, or 250 GB 7200 rpm hard disk drives
Embedded NICs	Two 10/100/1000 WOL network interface controllers
SCSI controller	One SCSI controller for tape backup

<u>top</u>

Physical specifications

Height	4.32 cm (1.71 inches)	
Width	42.86 cm (16.87 inches)	
Depth	59.69 cm (23.5 inches)	
Weight	19.16 kg, 42.25 lb shipping	
	12.24 kg, 27 lb out of box	

<u>top</u>

Electrical specifications

Dense Line Malteres	
Range Line Voltage	90 to 132 VAC/180 to 265 VAC
Nominal Line Voltage	100 to 120 VAC/200 to 240 VAC
Line Frequency	50 to 60 Hz
Rated Input Power	250 Watts (maximum)
Typical Input Current	2.5 Amps (100 VAC) , 1.3 Amps (200 VAC)

<u>top</u>

Environmental specifications

	Operating 41 to 95°F (5°C to 35°C) Shipping -40 to 158°F (-40°C to 70°C)
Relative Humidity (non-condensing)	10 to 80% @ 82°F (28°C) (wet bulb) 90% @ 82°F (28°C) (wet bulb)

<u>top</u>